

Buret, Automatic, Self-Zeroing, 25 mL Buret Capacity



Продукт №:

2087640

Свържете се с нас

ВGN Цена: Не е показана дата на доставка

Durable, crystal-clear acrylic buret is calibrated to meet ASTM E287 requirements. Leak-proof stopcock with self-lubricating PTFE TFE plug. Unaffected by dilute mineral acids and bases (except hydrofluoric acid and ammonium hydroxide). Handles liquids with a pH range of 1 - 14 and up to 5% wt/wt of acids or 30% bases can be used. Not designed for exposure to alcohol or organic solvents. Includes low density polyethylene squeeze bottle and 36" tubing for easy self-zeroing set up for titration work stations. Dust cover included.

Calibrated

Individually calibrated to meet accuracy of ASTM* E287 for repeatable, accurate results

Chemical compatibility

Can be used with dilute mineral acids and bases except hydrofluoric acid and ammonium hydroxide

Wide pH range

pH range of 1 - 14 is ideal; compatible with up to 5% wt/wt acids and up to 30% bases accomodating a wide range of tirants

All-inclusive buret kit

Comes complete with everything you need to get started: acrylic buret, LDPE squeeze bottle assembly, 3 ft. (91 cm) PVC tubing, and buret cover

Easy to read

Transparent/Graduated

Спецификации

Капацитет:	25 mL
Материал на тялото (измервателния уред):	Glass
Специална функция:	Buret, Automatic, Self-Zeroing