



QP1680 High-Temperature TOC Laboratory Analyser, with auto sampler, 65 positions

Продукт №: **LPV448.99.00001**

BGN Цена: Свържете се с нас

Не е показана дата на доставка

The QP1680 is available as a combined TOC and TN_b analyser or for the individual parameters TOC or TN_b.

The most important features include:

- Direct sample injection eliminates sample contact with valves and the built-in injection syringe, which minimizes the risk of sample carry-over.
- Large diameter sample aspiration tubing can handle particles up to 800 µm, expanding possible applications and reducing clogging.
- Integrated stirrer for each sample position homogenizes particle-containing samples before injection.
- Small footprint with integrated 65-position auto-sampler requires less space in the laboratory (an auto-sampler with 96 positions is also available as an alternative).
- Simple operation, data analysis and system diagnosis thanks to an intuitive software package.

Спецификации

Analysis time: Approx. 3 minutes

Gas consumption: 150 mL/min*

*Sample preparation for NPOC determination requires additional 300-350 mL/min.

Gas specifications: Oxygen or synthetic air: minimum 99.998% (4.8) at 3 - 10 bar

Number of sample positions: 65

Oxidation method: Catalytic combustion at 680 °C

Гаранция: 24 месеца

Граница на откриваемост: TC, TOC, NPOC: 50 µg/L

Замърсяване, степен: 2

Захранване: Analyser: 750 W max.

PC: 90 W max.

Monitor: 100 W max.

Измерване метод: NDIR (non-dispersive Infrared Detection)

Измерване, диапазон: TC, TIC, NPOC: 0 - 30000 mg/L

Какво има в кутията: TOC Instrument

Sample tray with 65 positions for 40 mL vials

	Glass sample vials 40 mL (100 pcs)
	USB 2.0 cable A-B
	Set of tubing PTFE blue-stripe 1/8" OD length 2 m including nut & ferrule
	Reagent container with screwcap for UPW, Acid and Waste
	Power cord
	USB storage device with software, test results and Full User Manual
	Printed User Manual
Модел:	QP1680-TOC
Норми и стандарти:	TOC / NPOC: ASTM D7573, EN 1484, EPA 415.1, EPA 9060A, ISO 8245, SM 5310B, NEN-ISO 20236
Обем на проба:	10 - 1000 µL
Околна температура:	-20 - 60 °C
Параметър:	TOC
Пауза:	Analyser: 100 - 240 VAC, 50/60 Hz, 16 A, with protective grounding
	PC: 100 - 240 VAC, 50/60 Hz, 1.6 A, with protective grounding
	Monitor: 100 - 240 VAC, 50/60 Hz, 1.6 A, with protective grounding
Повторяемост:	Up to 10 mg/L TC, TIC, NPOC, TN: < 5%
	> 10 mg/L TC, TIC, NPOC, TN: < 2%
Размери:	440 mm x 380 mm x 700 mm (H x W x D)
Тегло:	Approx. 31 kg
Температура:	Furnace temperature max. 1050 °C (depending on configuration)
Условия на работа:	20 - 30 °C; 20 - 80% relative humidity (non-condensing)

Какво има в кутията

TOC Instrument
Sample tray with 65 positions for 40 mL vials
Glass sample vials 40 mL (100 pcs)
USB 2.0 cable A-B
Set of tubing PTFE blue-stripe 1/8" OD length 2 m including nut & ferrule
Reagent container with screwcap for UPW, Acid and Waste
Power cord
USB storage device with software, test results and Full User Manual
Printed User Manual

Задължителни аксесоари

- QP1680 TOC/TNb Starter Package (Item SMKIT500000)